



All Falco car bridges comply with the NEN-EN1493 safety standard and are supplied with a Dutch manual including maintenance protocol and CE certificate 2006/42/EG.



Pump unit protective cover



Including LED bridge lighting

Technische specificaties

capacity	4000 kg
voltage	230V 1-Fase
motor power	2,2 kw
min. ramp height	185 mm
max. lifting height	1850 mm
length of the lanes	4516 mm
width of the lanes	508 mm
distance between the lanes	900mm
distance between the columns	2715mm
height of the columns	2370mm
lifting time	+/- 120 seconds

Centurion 4000kg 230V

Four column lift bridge 4,5m

VL4K400V



- Pump unit protective cover
- Low ramp height
- Passage width 2.7 m
- High safety factor
- Incl LED bridge lighting



This Falco Sollevatori four column lift bridge is of high quality and extremely suitable for professional use. At Falco lift bridges, quality and finish come first.

This 4 column lift bridge has the pump unit at the top of the column to save space. The model has a double locking system, which guarantees the safety of people and equipment.

Thanks to its robust construction and well thought-out design, this four-column lift bridge is equipped with useful features.

Features

- Pneumatic central unlocking
- Produced according to NEN 1493, suitable for APK
- Adjustable lanes
- Foot protection by acoustic signal
- Including LED bridge lighting
- Includes rail for bridge jack

